BEVERAGE-AIR

BLAST CHILLER

Chills, Freezes, and more!

Shown with optional ramp

R290 REFRIGERANT

Stainless Steel Exterior And Interior
Rounded interior corners for proper cleaning

High Density, Polyurethane Insulation

Hinged Door With Gasket
with Closing Ramp System and Ergonomic Vertical Door Handle

Anti-Condensation Resistance
Placed On The Door Under The Gasket

Stainless Steel Door Liner

Thick Stainless Steel Internal Bumper
to Avoid Damage Caused By The Cart

Die-Formed Leak-Proof Floor

Heated Core Probe
with 4 Measuring Points

Customized Blast Chilling and Blast Freezing
100 cycles can be memorized

USB Connection
for Uploading And Downloading Data And Recipes

BLAST CHILLER

CHILLS, FREEZES, AND MORE!

ROLL-IN BLAST CHILLER/FREEZERS

MODEL #	DOORS/ SHELVES	WIDTH	DEPTH	HEIGHT	VOLTS	HP	AMPS	CUBIC FEET	CHILLING CYCLE	CHILLING CAPACITY
RCBL-202-R-PFA-HC	1/0	43.31	64	94.5	208	1 1/4 x 3	13.2	49.95	160° to 38° F (90 minutes)	242.6 lbs

Depth measurement includes handles. Height measurement includes mounting height.

5" HIGH DEFINITION, EASY-TO-USE TOUCH DISPLAY

BLAST CHILLING AND SHOCK FREEZING

SELF-CONTAINED R290 REFRIGERATION SYSTEM

EXPANDABILITY AND CONTROL
easily add, edit or rename recipes, all organized by product type and function

TOUCH CONTROL PHOTO MENU
is easy to use, and the function selection is immediate and intuitive

Shown with optional ramp

EXTERIOR FINISHES
- Stainless steel

INTERIOR FINISHES
- Stainless steel

INTERIOR SPACE CAPACITY
- Maximum Interior Dimensions for Carts: 35"W x 40"D x 74"H (not included)

AVAILABLE ACCESSORIES
- Additional Single Sensor Probe
- Stainless steel ramp

AGENCY CERTIFICATIONS

Intertek Intertek

BEVERAGE-AIR

888-845-9800 BEVERAGE-AIR.COM

WELBILT
an ALI Group Company