



# BEVERAGE-AIR®

## CROSS TEMP® SERIES

### Easily converts from refrigerator to freezer

#### WHAT IS CROSS TEMP® TECHNOLOGY?

New from Beverage-Air, Cross Temp™ technology allows the user to easily switch the unit back and forth from refrigerator to freezer as needed, with a range of -15° to 40°F.

#### THE PURPOSE OF CROSS TEMP®

Simply put, Cross Temp technology lets the user get the most flexibility from the unit, by letting them switch from fridge to freezer as their menus change with the seasons and initiatives, including ice-cream storage.

#### IS CROSS TEMP ENERGY EFFICIENT?

The Cross Temp® units are intuitive and self-adjust for optimal effectiveness based on usage. Even in high-usage situations, Cross Temp units adjust to maintain maximum energy efficiency.

#### HOW LONG DOES THE CONVERSION TAKE?

On average, a Cross Temp unit can convert from refrigerator to freezer or vice versa, in under an hour. (Conditions and results will vary)



**Variable speed compressor technology achieves 30% more energy efficiency compared to a single-speed**

**Temperature range of -15 to 40° F**

**Modulates coil temp to achieve desired set point while achieving maximum energy efficiency**

**Single cabinet configurable to all menu initiatives**

**Intuitive compressor**  
adjusts for optimal effectiveness in high-use situations

**Quicker pull-down**  
for both air and product temperatures

**Improved product stability**

**Smart-defrost and Expansion valve**

**Rapid-recovery after defrost**  
consistent product temperature and ensures food quality

**Door locks standard**  
Solid doors only (optional on glass door models)

**Field-reversible doors**  
(except for CT12-12HC models)

**Featuring environmentally friendly energy efficient R290 refrigerant**



**888-845-9800 beverage-air.com**

# CROSS TEMP® SERIES

Easily converts from refrigerator to freezer

## 1 SECTION & COMPRESSOR

CAN CONVERT BETWEEN FREEZER AND REFRIGERATOR  
TEMPERATURES FROM -15° TO 40°F

MODEL WIDTH	DOOR TYPE	MODEL #	DOORS/ SHELVES	VOLTS	HP	AMPS	CUBIC FEET	WIDTH	DEPTH	HEIGHT	CRATED WEIGHT
<b>26"</b> 1 SECTION	SOLID	CT1HC-1S	1/3	115	4/5	8	23.1	26	33.63	78.5	326
	HALF SOLID	CT1HC-1HS	2/3								324
	GLASS	CT1HC-1G	1/3	115	4/5	8	23.1				429
	HALF GLASS	CT1HC-1HG	2/3								356

Depth measurement includes handles.  
For total height, add 3 or 6 inches, based on your mounting choice.

## 2 SECTIONS & COMPRESSORS

CAN CONVERT BETWEEN FREEZER AND REFRIGERATOR  
TEMPERATURES FROM -15° TO 40°F

MODEL WIDTH	DOOR TYPE	MODEL #	DOORS/ SHELVES	VOLTS	HP	AMPS	CUBIC FEET	WIDTH	DEPTH	HEIGHT	CRATED WEIGHT
<b>27"</b> 2 SECTIONS (STACKED)	HALF SOLID	CT12-12HC-1HS	2/4	115 (X2)	1: 1/3 2: 1/3	1: 7.5 2: 7.5	1: 9 2: 9	26.5	34.88	78.13	438
	HALF GLASS	CT12-12HC-1HG	2/4								360

Depth measurement includes handles.  
For total height, add 6 inches for your mounting choice.



**EASY-TO-USE CONTROLLER**  
to quickly adjust set points



**VARIABLE SPEED SYSTEM**  
modulates coil temp

### EXTERIOR FINISHES

- Stainless steel front with continuous coil coated sides
- Stainless steel sides/front

### INTERIOR FINISHES

- Corrosion resistant aluminum
- Stainless steel

### AVAILABLE ACCESSORIES

- Tray Slides
- Additional shelves

### MOUNTING OPTIONS

- 6" casters (standard)
- 6" legs
- 3" casters (single section only)
- Flanged/seismic feet

### AVAILABLE DOORS

- Solid (one full-door)
- Half Solid (two half-doors)
- Glass (one full-door)
- Half Glass (two half-doors)

### AGENCY CERTIFICATIONS



### AVAILABLE OPTIONS

- Left hand hinge doors

CTIS-20221019

**BEVERAGE-AIR®**

**888-845-9800 beverage-air.com**

an Ali Group Company



The Spirit of Excellence