



# BEVERAGE-AIR

Project:.....	AIA#
Item:.....	
Location:.....	SIS#
Approved:.....	

## TOP MOUNT DUAL TEMPERATURE

MODEL:  
PRF12-12HC-1HS

PRF12-12HC Solid Half-Doors Refrigerator/Freezer  
Hydrocarbon Series



**3 Year Parts/Labor Warranty**  
**Additional 4 Year Compressor Warranty**

### CABINET CONSTRUCTION

- Stainless steel exterior door, sides, and front (galvanized top, back & bottom)
- Interior corrosion resistant aluminum
- Stainless steel door liner
- Full electronic control with exterior digital thermometer
- Expansion valve technology
- Variable speed technology
- Stainless steel braker covers
- Dual temp refrigerator/freezer units provide two different operating temperature zones for different types of products
- Top side refrigerator
- Bottom side freezer
- Self-closing doors on cam-lift hinges, with 120° hold open feature
- One-piece snap-in magnetic door gaskets for positive seal
- Door locks standard
- Three (3) heavy-duty epoxy coated shelves per section
- 6" Legs

### OPTIONS & ACCESSORIES

- Stainless steel back
- Stainless steel interior
- Zone Operating temperature configuration (R/R, F/R, F/F)
- Tray slide kit
- Left and right hand door swing (at time of order)
- 6" Casters or seismic/flanged legs
- Remote option\* (see note on back page)

### REFRIGERATION SYSTEM

- Uses environmentally friendly, energy efficient R290 refrigerant and meets all regulatory requirements for CARB, SNAP, DOE & more
- Hot gas condensate evaporator
- Adaptive defrost
- Epoxy coated evaporator coil

PRF12-12HC TOP MOUNT DUAL TEMP REACH-IN



Please verify qualifying units by visiting:  
[www.energystar.gov/cfs](http://www.energystar.gov/cfs)

3779 Champion Blvd., Winston-Salem, NC 27105  
1-888-845-9800 Fax: 1-336-245-6453  
Beverage-Air.com Sales@bevair.com



# BEVERAGE-AIR

MODEL	PRF12-12HC-1HS
<b>EXTERNAL DIMENSIONAL DATA</b>	
Width Overall	26 <sup>5</sup> / <sub>8</sub> "
Depth Overall with Handle	34 <sup>5</sup> / <sub>8</sub> "
Height Overall	84 <sup>3</sup> / <sub>4</sub> "
Number of Doors	2
Depth with Door Open 90°	57 <sup>5</sup> / <sub>8</sub> "
Door Opening (in)	21 <sup>1</sup> / <sub>2</sub> " x 24 <sup>5</sup> / <sub>8</sub> "
<b>INTERNAL DIMENSIONAL DATA</b>	
NET Capacity Refrigerator (cubic ft.)	9.0
NET Capacity Freezer (cubic ft.)	9.0
Internal Width Overall (in)	(2) 22 <sup>1</sup> / <sub>2</sub> "
Internal Width Overall (in)	26 <sup>1</sup> / <sub>8</sub> "
Internal Height Overall Top (in)	26 <sup>5</sup> / <sub>8</sub> "
Internal Height Overall Bottom (in)	22 <sup>3</sup> / <sub>8</sub> "
Number of Shelves	4
<b>ELECTRICAL DATA</b>	
Full Load Amperes Refrigerator	7.5
Full Load Amperes Freezer	7.5
<b>REFRIGERATION DATA</b>	
Horsepower* Refrigerator	1/3
Horsepower* Freezer	1/3
Capacity (BTU/Hr)* Refrigerator/Freezer	Variable Speed Technology
<b>SHIPPING DATA</b>	
Gross Weight - Crated lbs	399 lbs
Height - Crated	88"
Width - Crated	45"
Depth - Crated	36"

\*NOTE: Remote units are field wired and comes with 6" legs.  
Refrigerant must be specified at time of order.

## Top Mount Dual Temp Reach-In Model: PRF12-12HC-1HS

**Model Views**

Required Clearance: Top 12", Rear 3", Sides 0"

**PLAN VIEW**

**ELEVATION VIEW**

**SIDE VIEW**

### \*ELECTRICAL CONNECTION



**115/60/1  
(2) NEMA 5-15P**

Unit pre-wired at factory and include 8' long cord and plug set.



3779 Champion Blvd., Winston-Salem, NC 27105 1-888-845-9800 Fax: 1-336-245-6453 Beverage-Air.com Sales@bevair.com

an Ali Group Company



The Spirit of Excellence